

GRABBER

GRABBER .

GRABBER , . .

GRABBER:

+12V	+12V
+3.3V	+3.3V
+5V	+5V
-12	-12V
-5V	-5V
CPU_FAN	
CPU_TEMP	
SYS_TEMP	MB
UPS_COMMLOST	
UPS_FATAL_ERROR	
UPS_LOWBATT	
UPS_ONBATT	
UPS_ONLINE	
UPS_REPLACEBATT	
UPS_SHUTTING	
VCORE	
AUDIO_SIG_LOST	
CONNECT_FAIL	
CONNECT_OK	
NETWORK_FAILURE	
STATE_CONNECTED	

GRABBER :

-		
---	--	--

"SETUP" –	chan<>	PCI (0,1,2,...,32)
	mode<>	/ (0 – , 1 – , 2 –)
	resolution<>	: 0 – , (384x288); 1 – , (768x288); 2 – , (768x576)
	format<>	(PAL, NTSC)
	drives<>	(DRIVE1:\, DRIVE2:\ ... DRIVEN:\)
	cams<>	
	auth<>	
	ip<>	IP-
	name<>	
	flags <>	
	ip_port<>	IP-
	password<>	
	type<>	
	username<>	
	watchdog<>	WatchDog (0 – , 1 –)
"SET_DRIVES" –	drives<>	
"MUX1_OFF" – 1	-	-
"MUX2_OFF" – 2	-	-
"MUX3_OFF" – 3	-	-
"SET_IPINT_PARAM" – () IP-. IP-, web-. . (. ,), 2. param_id param_value SET_IPINT_PARAM	param_id<>	. – . 2. param_id param_value SET_IPINT_PARAM
	param_value<>	. – . 2. param_id param_value SET_IPINT_PARAM
	cam_id<>	
	vstream_id<>	(). " " " ", 1.1, 1.2.
"START" –	-	-
"STOP" –	-	-
"ENABLE" – ()	recursive<>	: 0 – 1 – ,

"DISABLE" – ()	recursive<>	: 0 – 1 – ,
--------------------	-------------	----------------------

GRABBER :

GRABBER	
ID<>	
PARENT_ID<>	