

## MACRO

### 1. HTTP API

IP- 192.168.0.13.


```
:  
192.168.10.101/httpapi/SendPTZ?action=sendptz&PTZ_PRESETSET=85  
:  
192.168.10.101/httpapi/SendPTZ?action=sendptz&PTZ_PRESETSET=86
```

JScript.

```
function DoPreset(preset)  
{  
    xmlhttp=new ActiveXObject( "MSXML2.XMLHTTP" );  
    if(xmlhttp == null)  
    {  
        return;  
    }  
    xmlhttp.open( "GET", "http://192.168.0.13/httpapi/SendPTZ?action=sendptz&PTZ_PRESETSET="+preset, false,"admin","1234" );  
  
    xmlhttp.send();  
    DebugLogString(xmlhttp.status);  
}  
if (Event.SourceType == "MACRO" && Event.SourceId == "6" && Event.Action == "RUN")  
{  
    DoPreset("85");  
}  
  
if (Event.SourceType == "MACRO" && Event.SourceId == "7" && Event.Action == "RUN")  
{  
    DoPreset("86");  
}
```

### 2. HTML-

1 detected.png found.jpg C:\\Pictures\\ example@gmail.com. :



detected.png found.jpg

```
if(Event.SourceType == "MACRO" && Event.SourceId=="1" &&Event.Action=="RUN" )
{
var file1 = "detected.png";
var file2 = "found.jpg";
var file_folder = "C:\\\\Pictures\\\\";

var test_event = CreateMsg();
test_event.StringToMsg( "MAIL_MESSAGE|1|SEND_RAW|cc<>,to<example@gmail.com>,objname< 1>,subject<>,parent_id<1>,flags<>,pack<>,name< 1>,from<server@itv.ru>,_marker<>" );

test_event.SetParam("body", "<html><body>\r\n<h3>Face found</h3>\r\n<table><tr>\r\n<td>Detected</td><td>Found in DB</td>\r\n</tr><tr>\r\n<td><img width='200' alt='image1' src='cid:" + file1 + "'></td>\r\n<td><img width='200' alt='image2' src='cid:" + file2 + "'></td>\r\n</tr></table>\r\n</body></html>");
test_event.SetParam("attachments",file_folder+file1+";" + file_folder+file2);
test_event.SetParam("is_body_html", 1);
DoReact(test_event);
}
```